

Since 1977

Energy efficiency & MAX imum performance

HONDA ENGINES

GAS DRIVE SERIES

 Quiet, low RPM Solid Cast Iron construction for extended life up to 50,000 hours*



Flow-Tek™ Concentric Disc Valves for Maximum Performance & Longevity



Air-Stream Technology™ For up to 50% longer life



Electric start standard on all models over 8HP

Contact:



www.EmaxCompressor.com 1000 Cass Drive Clayton, Ohio 45315 Toll Free: 866-294-4153 Fax: 937-540-1150 sales@emaxcompressor.com





Features & Benefits

- Cool-Tek: The coolest running compressors in the industry 35% lower operating temperature reduces moisture build up & extends pump life
- Belt Tension Adjuster: Fast, easy "one turn" way to tighten belts which reduces vibration and extends belt life

Model	FGPS0817WL	EGES0817Wh	EGES1330ST	FGES1830ST	EGES1860ST	FGFS2#80ST
Running HP	8	8	13	18	18	24
SCFM	18	18	24	34	34	52
Engine RPM	3200	3200	3200	3200	3200	3200
Electric Start	No	Yes	Yes	Yes	Yes	Yes
Tank size (Gallons)	17	17	30	30	60	80
Maximum PSI	150	150	175	175	175	175
Pump Model	APP2V0732\$	APP2V0732\$	APP3Y0732T	APP4V1043T	APP4V1043T	APP3Y2062T
Outlet	NPT 3/4"	NPT 3/4"	NPT 3/4"	NPT 3/4"	NPT 3/4°	NPT 1"
Weight (lbs.)	275	275	395	540	610	870
Pump RPM	650	650	820	800	800	640
Dimensions: LxWxH	46"x21"x37"	46"x21"x37"	51"x23"x40"	44"x23"x44"	51"x23"x50"	72"x25"x6(l"

* Baretin: E-10 Bearing Raling

18 & 24HP Compressors do not include gas tank

5YA - Limited warrenty on oil-lubriceted eir compressor pumps and tento.

2YH - Limited warranty on all air compressor components.







